



Tek-Rail™



320 Temple Ave., Newnan, GA 30263 678-854-0510 FAX 678-854-0519

Tek-Rail Care & Maintenance Instructions

Care / Maintenance Instructions:

Clean aluminum twice a year. Clean aluminum on coastal applications at least every other month. Product in extreme environments should be cleaned monthly. Clean with a non-abrasive, pH neutral detergent solution. Always rinse with fresh water to remove any residue of soap. Avoid using a dry sponge, which may scratch the surface. Always remove sap, tree seeds, bugs, bird droppings, and etc., as soon as possible, as sun exposure and heat will make them more difficult to remove. Certain household cleaners, abrasive agents, harsh chemicals, strong solvents, acids, steel wool, and industrial cleaners can cause damage and discoloration to the finish and are not recommended. ALWAYS, test a small, inconspicuous area before applying any product to the aluminum material. Never power wash on high settings, only the lowest setting. Be sure to never exceed 400 PSI. Please maintain files with receipts and date of purchase and use of the nonabrasive cleaners, and the pH neutral detergent solutions used for warranty purposes. If power washer is used, track the brand name, model, and PSI setting used.

Cleaning Log:

Date Cleaned	Type Of Cleaner	Cleaner Receipt Attached	Method of Cleaning	Other Information Tracked

